



Lloyd's
Register

Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

This certificate supersedes certificate number 99/20021 (E4) issued on 29.04.2015 which is hereby cancelled.

This certificate is issued to:

PRODUCER

TPR Fiberdur GmbH & Co. KG
Industriepark Emil Mayrisch
Galileo-Allee 6
52457 Aldenhoven
Germany

DESCRIPTION

Glass fibre reinforced epoxy pipe system, which is filament wound and at high temperature cured, conductive or non-conductive.
Joint types: conical or cylindrical adhesive bonded, laminated and flanged types, mechanical couplings and rubber seal lock joints.
Fire barrier to be added for small sizes to obtain fire endurance level L3.

STANDARD

Lloyd's Register Rules and Regulations for the Classification of Ships,
July 2019;
IMO Resolution A 753 (18)

Certificate No.

99/20021 (E5)

Issue Date

11 July 2019

Expiry Date

31 July 2024

Sheet

1 of 5

Lloyd's Register EMEA

71 Fenchurch Street, London EC3M 4BS



LR031.1.2016.06

Torsten Schröder
Hamburg Technical Support Office
Lloyd's Register EMEA

Lloyd's Register EMEA
Is a subsidiary of Lloyd's Register Group

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as the 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.



TYPES

Fiberdur EP = GRE system (additional liner of 0.5 mm)
Fiberdur CSEP = GRE system (additional liner of 2.5 mm)

EP = GRE, Conductive and non-conductive	Nominal Pressure [bar]
EP, CS EP	PN 10 or PN 16
EP Fibermarine, CS EP Fibermarine	PN 10 or PN 16
EP Fibermarine HighLine, CS EP Fibermarine HighLine	PN 16

Nominal Diameter range: DN 25 to DN 800

APPLICATION

In ships and offshore installations classed or intended for Classification with Lloyd's Register in the following locations:
Open decks, within tanks, cofferdams, void spaces, pipe tunnels, ducts and further locations, where fire endurance tests according to Appendix 2, Level 3 and flame spread test acc. to Appendix 3 of the IMO Resolution A.753 (18) are required.

Certificate No. 99/20021 (E5)
Issue Date 11 July 2019
Expiry Date 31 July 2024
Sheet 2 of 5




Torsten Schröder
Hamburg Technical Support Office
Lloyd's Register EMEA

LR031.1.2016.06

Torsten Schröder
Hamburg Technical Support Office
Lloyd's Register EMEA

Lloyd's Register EMEA
71 Fenchurch Street, London EC3M 4BS

Lloyd's Register EMEA
Is a subsidiary of Lloyd's Register Group

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as the 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.



RATINGS

Pipes structural wall thickness [mm]
(excluding internal liner 0.5 or 2.5 and top coat 0.3 mm)

DN	EP 10 CS EP	EP 16 CS EP	EP Fibermarine, CS EP Fibermarine PN10, 16 Collapse pressure 3 bar	EP Fibermarine Highline, CS EP Fibermarine Highline PN16 Collapse pressure 12 bar
25	1.6	1.6	1.6	1.6
40	1.6	1.6	1.6	1.6
50	1.6	1.6	1.6	1.6
65	1.6	1.6	1.6	1.9
80	1.6	1.6	1.6	2.3
100	1.6	1.6	1.8	2.9
125	2.0	2.0	2.3	3.6
150	1.6	2.4	2.7	4.3
200	2.0	3.2	3.6	5.7
250	2.4	3.6	4.5	7.1
300	3.2	4.8	5.3	8.5
350	4.0	5.6	6.2	9.9
400	4.0	6.4	7.1	11.3
450	4.8	7.2	8.0	12.7
500	4.8	7.2	8.8	14.2
600	5.6	8.8	10.6	17.0
700	6.4	10.4	12.4	19.8
800	7.2	12.0	14.1	22.6

Certificate No. 99/20021 (E5)
Issue Date 11 July 2019
Expiry Date 31 July 2024
Sheet 3 of 5



LR031.1.2016.06

Torsten Schröder
Hamburg Technical Support Office
Lloyd's Register EMEA

Lloyd's Register EMEA
71 Fenchurch Street, London EC3M 4BS

Lloyd's Register EMEA
Is a subsidiary of Lloyd's Register Group

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as the 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.



RATINGS, cont.

Max. internal pressure (bar) depending on temperature:

Temperature:	-50 to +80°C	at 95°C
EP 10, CS EP 10 EP Fibermarine 10 CS EP Fibermarine 10	10	6
EP 16, CS EP 16 EP Fibermarine 16 CS EP Fibermarine 16 EP Fibermarine Highline 16 CS EP Fibermarine Highline 16	16	10

intermediate values may be obtained by interpolation

EP and CS EP pipes are not collapse resistant.

The Fibermarine pipe withstand full vacuum with safety factor 3:1. (collapse pressure is 3 bar.)

The Fibermarine HighLine withstand full vacuum plus 3 bar external pressure with safety factor 3:1 (collapse pressure is 12 bar.)

A **Fire Barrier** to be added for fire endurance level L3 as follows:

Type of connection	Size of range DN	Fire Barrier ¹
Conical to cylindrical pipe adhesive bounded joint	25 up to 50	10 mm
	> 50 up to 100	5 mm
	> 100 up to 152	2,5 mm
	> 152	None

Footnote¹ - Final layer of VE / glass laminates

Other Conditions

The Installation of the piping system is to be carried out by well trained personnel in accordance with the instructions and recommendations of the manufacturer respectively in accordance with the installation requirements of the IMO Resolution as applicable.

Certificate No.	99/20021 (E5)
Issue Date	11 July 2019
Expiry Date	31 July 2024
Sheet	4 of 5



LR031.1.2016.06

Torsten Schröder
Hamburg Technical Support Office
Lloyd's Register EMEA

Lloyd's Register EMEA
71 Fenchurch Street, London EC3M 4BS

Lloyd's Register EMEA
Is a subsidiary of Lloyd's Register Group



Lloyd's
Register

The Type Approval does not eliminate the need for normal inspection and survey procedures required by the Rules and Regulations.

If the specified standards are amended during the validity of this certificate, the product is to be re-approved prior to it being supplied to vessels to which the amended standards apply.

The Design Appraisal Document No. ENS 20450-07, Issue No. 4 and its supplementary Type Approval Terms and Conditions form part of this Certificate.

Certificate No.	99/ 20021 (E5)
Issue Date	11 July 2019
Expiry Date	31 July 2024
Sheet	5 of 5

*Lloyd's Register EMEA
71 Fenchurch Street, London EC3M 4BS*



Torsten Schröder
Hamburg Technical Support Office
Lloyd's Register EMEA

LR031.1.2016.06

Torsten Schröder
Hamburg Technical Support Office
Lloyd's Register EMEA

Lloyd's Register EMEA
Is a subsidiary of Lloyd's Register Group

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as the 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.